FROMM | PACKAGING SYSTEMS

Datasheet P404

Manual plastic strapping tools

Manual plastic strapping tools

Characteristics

Strapping qualities:		Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths thicknesses	15.0 – 16.0 mm / $^{5}/_{8}$" 0.50 – 0.90 mm / .020 - .035"
Weights:		3.8 kg / 8.4 lbs without suspension 3.9 kg / 8.6 lbs with suspension
Average seal strength:		approx. 70 %
Type of joint:		Joint with special seals
Suspension (Optional):		bolt and grip ball for horizontal applications; have to be ordered separately

Advantages

- Handy light weight tensioning and sealing tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages) using plastic strapping
- A reliable, robust and service – friendly tool
- The windless tensioning system allows very high strap tension
- Special serrated seals and the patented sealing force balance system guarantee a very high seal joint efficiency
- The sealing handle is always operated until it hits the stop – thus the seal efficiency of all joints is high and balanced

NANDEE STRAPAC | PACKAGING PARTNER

NANDEE-STRAPAC CO., LTD.
310, 312 Soi Chan 32, Chan Road, Thung Wat Don, Sathorn, Bangkok 10120
Tel : 0-2675-5543-4, 0-2675-6656-7, 0-2675-6990 Fax : 0-2672-3266
E-mail : strapac@nandee.co.th

FROMM | PACKAGING SYSTEMS

Datasheet P404

Manual plastic strapping tools

Chart of types model P404

Item No.	Model	Width		Thicknesses	
		mm	inch	mm	inch
43.0404	P404/15-16/0.50-0.90	15-16	5/8“	0.50-0.90	.020-.035

Seals

Item No.	Model	Width		Contents of	Weight	
		mm	inch	carton in pcs.	kg	lbs
41.5082	P404/16	15-16	5/8“	1000	9.3	20.5

Accessories

P40.2046	Handle for horizontal applications (Grip ball and bolt)

NANDEE STRAPAC | PACKAGING PARTNER

NANDEE-STRAPAC CO., LTD.
310, 312 Soi Chan 32, Chan Road, Thung Wat Don, Sathorn, Bangkok 10120
Tel : 0-2675-5543-4, 0-2675-6656-7, 0-2675-6990 Fax : 0-2672-3266
E-mail : strapac@nandee.co.th